

FLAGSHIP SMOOTH BANNER – BLOCKOUT 510



Flagship Smooth Banner Blockout is ideal for POP / POS display including indoor and outdoor banners and posters, delivering exceptional colour vibrancy, stability and tear resistance. No laminating required short term use.

FEATURES

- Excellent opacity
- 2 widths 1370 / 1600 mm
- Fast ink drying

APPLICATIONS

- indoor & outdoor posters
- POP display
- pull-up banners

PROPERTIES	VALUE	TEST STANDARD
Weight (gsm)	510	ISO3801:1977
Polyester Fabric	500x500 denier 9x9 fd per inch	DIN60001/DIN EN ISO2060
Coating	PVC	—
Tensile Strength	750N/5cm (L) 750N/5cm (W)	ISO527/3:1995
Tear Strength	160N/5cm (L) 130N/5cm (W)	ISO4674/1:2003
Adhesion Strength	60N/5cm	DIN53357:1982
Low Temperature	-30° C	ISO13934-1:1999
Heat Sealable (RF)	YES	DIN53354
Core	76mm (3 inch)	—
Print Conditions	20 – 30° C / 50% RH	—
Storage	15 – 25° C / 50% RH	—
Shelf Life	1 year in original pack and above conditions	—

PRINT



UV-CURABLE



LATEX



SOLVENT



ECO-SOLVENT